

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F02F 1/22, F02B 25/22	A1	(11) International Publication Number: WO 00/43660	(43) International Publication Date: 27 July 2000 (27.07.00)
--	----	---	---

(21) International Application Number: PCT/SE00/00057
(22) International Filing Date: 14 January 2000 (14.01.00)
(30) Priority Data:
9900138-0 19 January 1999 (19.01.99) SE
(71) Applicant (for all designated States except US): AKTIEBO-
LAGET ELECTROLUX [SE/SE]; S-105 45 Stockholm
(SE).
(72) Inventors; and
(75) Inventors/Applicants (for US only): ANDERSSON, Lars
[SE/SE]; Sjömilsgatan 16, S-421 37 Västra Frölunda (SE).
MARTINSSON, Pär [SE/SE]; Ravingatan 10 B, S-556 28
Jönköping (SE).
(74) Agents: ANDERSSON, Lars et al.; AB Electrolux, c/o
Husqvarna AB, S-433 81 Jönsered (SE).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU,
AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ
(Utility model), DE, DE (Utility model), DK, DK (Utility
model), EE, EE (Utility model), ES, FI, FI (Utility model),
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG,
MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE,
SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA,
UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT,
LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI,
CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.


*Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.*

In English translation (filed in Swedish).

(54) Title: CYLINDER FOR INTERNAL COMBUSTION ENGINE

(57) Abstract

The invention refers to a cylinder (1) for a two-stroke, crankcase scavenged combustion engine, comprising an inlet pipe (10) for air/fuel mixture, at least one transfer port (17), and at least one outer connecting port (18) intended to be connected to a connecting duct (not shown), whereby the outer connecting port (18) is arranged so that it can be connected to the mentioned transfer port (17) via a piston ported air passage. The outer connecting port (18) is located below the inlet pipe (10) and at least one wall passage (14) extends from the mentioned outer connecting port (18), obliquely upwards through the cylinder wall, to at least one connecting port (16). This design enables the cooling air to flow freely around the cylinder above the inlet pipe (10), which improves the cooling of the cylinder.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

CYLINDER FOR INTERNAL COMBUSTION ENGINE

5

Technical field

The subject invention refers to a cylinder for a two-stroke, crankcase scavenged internal combustion engine, comprising an inlet pipe for air/fuel mixture, at least one transfer port, and at least one outer connecting port intended to be
10 connected to a connecting duct, whereby the outer connecting port is arranged so that it can be connected to the mentioned transfer port via a piston ported air passage.

Thus, fresh air is added at the upper part of the scavenging ducts and is intended to serve as a buffer against the air/fuel mixture below. When the scavenging takes place, this air buffer is largely lost out into the exhaust outlet, thus reducing the
15 fuel consumption and exhaust emissions.

Technical background

Engines of the above mentioned type have ducts for fresh air designed
20 with connecting ports in the cylinder, usually one on each side of the piston. The air flow between these connecting ports and the scavenging ducts is controlled by the position of the piston by means of a recess in the piston, which in a defined piston position connects the connecting ports and the scavenging ducts' scavenging ports in the cylinder. In order for this piston control to function, it is necessary that the
25 connecting ports are positioned at a defined distance above the inlet port.

According to known technology, which for instance is illustrated in W098/57053, cylinders in engines of this type have therefore been designed with one or several air ducts positioned above the inlet pipe. However, this positioning, which is closer to the combustion chamber than the inlet pipe, entails that the air inlet in this
30 case is subjected to a relatively high temperature with air expansion and reduced delivery rate as a result. Furthermore, the air inlet disturbs the cooling air, which

usually can flow unimpeded around the cylinder above the inlet tube, with an even higher temperature as a result.

In accordance with another known variant, which is also illustrated in .W098/57053, the air inlet is designed with two air ducts, one on each side of the inlet.

- 5 In this case, the inlet has been located higher than usual, and to prevent the inlet being blocked by the piston, an aperture has been made in the piston, which allows a passage for the air/fuel mixture down into the crankcase, even when the piston's lower edge is positioned below the inlet. Consequently, this solution requires a considerably more complicated piston design.

10

Summary of the invention

The purpose of the subject invention is to create a cylinder to which it is possible to add fresh air to the scavenging ducts without causing the problem mentioned above.

- 15 This purpose is achieved according to the subject invention by means of a cylinder of the type mentioned initially, where an outer connecting port is located below the inlet tube and that at least one passage extends from the outer connecting port, obliquely upwards through the cylinder wall, to at least one connecting port.

- 20 In relation to the inlet pipe, the mentioned connecting port is located so that a satisfactory control of the air supply by the piston to the scavenging ducts is possible.

- 25 This design enables the cooling air to flow freely around the cylinder above the inlet tube, which improves the cooling of the cylinder. Furthermore, the fresh air is not subjected to the higher temperatures which prevail above the inlet pipe, since the wall passages pass from below and past the inlet pipe through the material of the cylinder wall.

Further advantageous cooling of the fresh air is obtained by means of the close contact with the inlet, where each passage 'winds itself' around the inlet pipe and is consequently cooled as a result of this.

- 30 In accordance with a preferred embodiment, the cylinder comprises two wall passages, which pass one on each side of the inlet pipe.

The two wall passages can be joined in a common outer connecting port, which in that case is located immediately below the inlet tube. This embodiment can be achieved with a minimal amount of material resulting in a light and inexpensive cylinder.

5 Each scavenging port is preferably located slightly above the corresponding connecting port, which entails that the fresh air at the passage between the connecting ports and the scavenging ports is made to flow obliquely upwards. The location of the air inlet, according to the subject invention, therefore gives the fresh air an advantageous flow direction for the piston
10 ported air passage, i.e. obliquely upwards, whereby unnecessary directional changes of the fresh air flow is eliminated.

 The inlet pipe is preferably directed obliquely downwards towards the cylinder. The wall passages, which are directed obliquely upwards and which pass the inlet tube, thereby pass the inlet pipe at a greater angle, preferably almost at a
15 right angle, which results in an even further reduction of material consumption. Furthermore, the obliquely downwards directed inlet pipe is favourable, since the air/fuel mixture taken in is made to flow down into the crankcase and consequently improve the lubrication of the big end bearing.

20 **Brief description of the drawings**

 The subject invention will be described in closer detail in the following with reference to the accompanying drawing figures, which for the purpose of exemplification show a preferred embodiment of the invention.

 Figure 1 is a basic outline of an engine with a cylinder in accordance
25 with an embodiment of the invention.

 Figure 2 illustrates by means of a perspective drawing a cylinder in accordance with a preferred embodiment of the invention.

 Figure 3 illustrates the cylinder in figure 2 from the front.

 Figure 4 illustrates the cylinder in figure 2 from the side.

Description of a preferred embodiment

A cylinder 1 is shown schematically in figure 1 in accordance with an embodiment of the invention, which cylinder is mounted on a crank case 2. A spark plug 3 is arranged at the top of the cylinder. A part of the connecting rod 4 can be seen in the crankcase and a part of the piston 5 can be seen in the cylinder. These parts are not shown in their entirety so that the components more closely related to the invention can be seen more clearly. Naturally, the cylinder also has an exhaust outlet connected to a muffler, which are not at all illustrated in the figures for the sake of clarity.

It should also be noted that the cylinder's position throughout the subject description shows the crankcase connection facing downwards and the spark plug's attachment point directed upwards. No major variations should normally occur concerning this orientation, however, this orientation shall still not be regarded as a restriction of the subject invention, which rather refers to the relative design of the cylinder's various parts.

Furthermore, the cylinder 1 is equipped with an inlet pipe 10, through which the air/fuel mixture is supplied to the cylinder from a carburettor (not illustrated). The cylinder 1 also has one or several wall passages 14 for supply of fresh air. Each wall passage 14 exits on the inside of the cylinder wall in a connecting port 16. In accordance with the invention, each wall passage 14 is orientated obliquely downwards in relation to the connecting port 16, and extends past the inlet pipe 10 to an outer connecting port 18 on the outside of the cylinder, which is located below the mouth 20 of the inlet pipe.

Furthermore, the cylinder has at least one scavenging port 17, which leads to a scavenging duct (not shown). The scavenging duct can be shaped radially out from the cylinder in a conventional way.

The cylinder's interaction with the engine's remaining, but not illustrated parts (e.g. carburettor, scavenging ducts, exhaust outlet and muffler etc.), is regarded as so well known to the skilled man that a more detailed description of these parts and their function as a whole is superfluous.

Figures 2-4 show the cylinder in figure 1 (still without scavenging ducts) in perspective as well as plane views from the front and the side.

The cylinder, which is shown in figure 2, comprises an essentially cylindrical body 22, which has a flange 24 at its lower part intended to be attached to the engine's crankcase 2 as well as having an attachment point 26 for the spark plug 3, in its top part.

In the illustrated example, the cylinder 1 has two wall passages 14, which are cast into the cylinder's material 28 and pass on each side of the inlet pipe 10. Both wall passages 14 join in a common outer connecting port 18 below the inlet pipe 10. A partition wall 19 separates the passages. The common outer connecting port is surrounded by a flange 30 for the connection of a connecting duct (not shown).

As illustrated in figures 2-4, the cylinder 1 has a number of cooling fins 32, distributed along the entire height of the cylinder. However, for the sake of clarity, only the fins on the cylinder's upper half are shown.

The entire cylinder 1 is preferably cast in one piece, even though a cylinder consisting of several different parts would be possible. The outer connecting port 18 and the inlet pipe 10 thereby form a relatively integrated unit in the form of a protruding section 34 from the cylindrical body 22. A device is established in this unit 34, e.g. tapped holes 35, for the connection of a connecting duct to the outer connecting port 18 as well as of a carburettor to the inlet pipe 10.

In the illustrated example, the inlet pipe 10 is directed obliquely upwards from the cylinder, while the outer connecting port 18 as well as the first part of the passage immediately inside the outer connecting port 18, are directed essentially perpendicularly to the cylinder.

It is especially evident from figure 2 how the wall passages 14 wind around the inlet pipe 10 and pass it at almost a right angle. As a result of this design, the amount of material needed in the protruding section 34 becomes relatively small.


It is evident that a number of modifications of the embodiment as described above are possible within the scope of the enclosed patent claims. For example, the exact path of the wall passages 14 through the material can vary as well as the dimensions and the angles of the inlet, passages and ports.

PATENT CLAIMS

1. Cylinder (1) for a two-stroke, crankcase scavenged internal combustion engine, including an inlet pipe (10) for air/fuel mixture, at least
5 one transfer port (17), and at least one outer connecting port (18) intended to be connected to a connecting duct (not shown), whereby the outer connecting port (18) is arranged so that it can be connected to the above mentioned transfer port (17) via a piston ported air passage, c h a r a c t e r i z e d in that the mentioned outer connecting port (18) is located below the inlet pipe (10) and that at least one wall passage (14)
10 extends from the mentioned outer connecting port (18), obliquely upwards through the cylinder wall, to at least one connecting port (16).
2. Cylinder in accordance with claim 1, whereby the cylinder includes two wall passages (14), which extend on each side past the inlet pipe (10).
3. Cylinder in accordance with claim 2, whereby the wall
15 passages (14) have a common outer connecting port (18).
4. Cylinder in accordance with claims 1-3, whereby the mentioned transfer port (17) is located somewhat higher than the corresponding connecting port (16).
5. Cylinder in accordance with any of the previous claims,
20 whereby the inlet pipe (10) is directed obliquely downwards towards the engine's crank case (2).
6. Cylinder in accordance with any of the previous claims, whereby the outer connecting port (18) is positioned essentially perpendicularly to the cylinder (1).

25

30

*Fig. 1*




Fig. 2




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00057

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: F02F 1/22, F02B 25/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: F02F, F02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9857053 A1 (KOMATSU ZENOAH CO.), 17 December 1998 (17.12.98), figures 1-11, abstract --	
A	EP 0391793 A1 (SOCIETE NOUVELLE RACING KART DEVELOPMENT "SOCIETE NOUVELLE R.K.D."), 10 October 1990 (10.10.90), figures 5-9, abstract --	
A	EP 0337768 A2 (TAIT, ROBERT JOHN), 18 October 1989 (18.10.89), figures 1-5, abstract --	

☒ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

- * Special categories of cited documents:
 - "A" document defining the general state of the art which is not considered to be of particular relevance
 - "E" earlier document but published on or after the international filing date
 - "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 - "O" document referring to an oral disclosure, use, exhibition or other means
 - "P" document published prior to the international filing date but later than the priority date claimed
 - "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
 - "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
 - "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
 - "&" document member of the same patent family

Date of the actual completion of the international search

25 April 2000

Date of mailing of the international search report

16-05-2000

Name and mailing address of the ISA
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Dan Ionesco / JA A
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00057

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 784866 A (THE VILLIERS ENGINEERING COMPANY LIMITED), 27 July 1935 (27.07.35), page 1, line 15 - line 40, figures 1-6 --	
A	FR 1434710 A (FICHEL & SACHS AKTIENGESELLSCHAFT), 28 February 1966 (28.02.66), page 1, figures 1,2 -- -----	

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/12/99

International application No.

PCT/SE 00/00057

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
WO	9857053	A1	17/12/98	AU 7550298 A	30/12/98
EP	0391793	A1	10/10/90	FR 2645207 A,B	05/10/90
EP	0337768	A2	18/10/89	NONE	
FR	784866	A	27/07/35	NONE	
FR	1434710	A	28/02/66	NONE	